



# RED LINE PROFESSIONAL-SERIES 5W30TD EURO MOTOR OIL



- Full-synthetic low-SAPS formula for passenger vehicles
- OEM-certified for use under vehicle warranty
- For extended drain intervals and fuel economy of the latest global gasoline/petrol and direct-injection diesel engines with particulate filters

## APPROVED / CERTIFIED:

API SN

**BMW**

LL-04

**PORSCHE C30**

**MERCEDES BENZ**

MB-Approval 229.51

**VW/AUDI**

507.00

504.00

## RECOMMENDED FOR:

**ACEA C3-12**

**MERCEDES BENZ**

MB 229.31

**CHRYSLER**

MS 11106

**GM**

dexos2®

dexos is a registered trademark of General Motors Corp.

## TYPICAL PROPERTIES:

ACEA Service Class	C3-12
API Service Class	SN
SAE Viscosity Grade (Motor Oil)	5W-30
Vis @ 100°C, cSt	12.2
Vis @ 40°C, cSt	80
CCS Viscosity, Poise, @-30 °C	5900
Pour Point, -39°C	-49
Pour Point, -38 °F	-56
HTHS Vis, cP @150°C, ASTM D4741	3.6

## PACKAGE SIZES:

12224 - 5W30TD Prof-Series - quart

12225 - 5W30TD Prof-Series - 5 quart

12228 - 5W30TD Prof-Series - 55 gallon

## ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

- FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks
- Low volatility for reduced oil consumption
- Long-life certification for reduced wear protection following factory drain intervals
- For high- and low-mileage engines
- Compatible with conventional and synthetic oils
- Withstands extreme temperatures

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM