



# RED LINE 5W40 MOTOR OIL



- Suitable for VW/Audi 505.01/505.00/502.00/501.01/500.00, BMW LL-01, water-cooled Porsche A40 and Mercedes-Benz 229.5/229.3/229.1 applications
- Thicker oil film at operating temperature than a petroleum 20W50
- Popular in turbocharged applications

## RECOMMENDED FOR:

**API SM/SN/SL/CF**  
**ACEA A3/B3/B4**

**Can-Am XPS**  
2014-2019

**Maserati** (API SL/CF  
and ACEA A3, B3 and  
B4)

**Mopar**  
05127394PB  
MS-10725  
MS-10850  
MS-10896  
MS-12991

**Porsche**  
A40  
C40  
503.01  
505.00-97  
505.01-99

**BMW**  
07 51 0 037 633  
07 51 0 038 649  
81 22 9 407 547  
LL-01  
LL-98

**Fiat** MS-12991

**Mercedes Benz**  
MB 229.1  
MB 229.3  
MB 229.5

**Nissan**  
KE900-90032  
KE900-90042

PSA B71 2296

**VW/Audi**  
500.00  
501.01  
502.00-97

**Hyundai**  
  
**Lexus**  
08880-82790  
08880-82800

## TYPICAL PROPERTIES:

ACEA Service Class	A3 B3/B4
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	5W40
Vis @ 100°C, cSt	15.6
Vis @ 40°C, cSt	97
Viscosity Index	174
CCS Viscosity, Poise, @ °C	58@-30
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @ 150°C, ASTM D4741	4.4

## PACKAGE SIZES:

- 15404 - 5W40 Motor Oil - quart
- 15405 - 5W40 Motor Oil - 1 gallon
- 15406 - 5W40 Motor Oil - 5 gallon
- 15408 - 5W40 Motor Oil - 55 gallon

## ABOUT RED LINE MOTOR OIL

- Full-synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM